


**Product:** X-LINE G/K LED 1300 PLX E 24 840 LINE-EL / L-572MM

**Index:** 19.4133.1121.24



## Description

The group of X-line luminaires is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaires may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.

## Product information

Category	<b>Recessed luminaires</b>
Family	<b>X-LINE G/K LED LINE</b>
Name	<b>X-LINE G/K LED 1300 PLX E 24 840 LINE-EL / L-572MM</b>
Index	<b>19.4133.1121.24</b>
EAN	<b>5902023879692</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>1420</b>
LED power [W]	<b>8</b>
Luminaire luminous flux [lm]	<b>947</b>
Power of luminaire [W]	<b>9</b>
Luminaire's light efficiency [lm/W]	<b>105,2</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 109° / 107,2°</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20/44</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000 (1) / 147000 (2)</b>
Lx/By	<b>L80/B10 (1) / L70/B50 (2)</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,9</b>
Circuit load capacity	<b>23 (B10), 36 (B16), 35(C10), 60 (C16)</b>

## Mechanical data



Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,5
Dimensions [mm]	572 x 80 x 136
Mounting hole [mm]	567 x 70

## A graph of light



## Accessories

Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires

