

Product: BERYL KN LED UP&DOWN 2x2,4W 5°-21° E IP40 34 830

Index: 19.4241.5211.34



## **Description**

Luminary adapted to be mounted on walls. High lighting efficiency LEDs were used as light sources. Optical system consists of professional lens that provide light distribution of  $5-21^{\circ}$  angle. Owing to the optical system solutions, the product is highly effective. Its body is made from anodized aluminum profile. It is resistant to solids, dust, and liquids penetration – IP40 or IP65. This type of luminary is recommended for decorative or accent illumination, e.g. in restaurants, pubs, or cafes.

### **Product information**

Category	Architectural luminaires	
Family	BERYL KN LED UP&DOWN	
Name	BERYL KN LED UP&DOWN 2x2,4W 5°-21° E IP40 34 830	
Index	19.4241.5211.34	
EAN	5902107035433	
















### Light and electrical data

Light source	LED
Luminous flux LED [lm]	310
LED power [W]	5
Luminaire luminous flux [lm]	249
Power of luminaire [W]	7
Luminaire's light efficiency [lm/W]	35,6
Color of the light [K]	3000
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 36° / 9,6°
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Circuit load capacity	80 (B10), 157 (B16), 265 (C10), 317 (C16)

#### Mechanical data





Assembly	mounted on wall
Material	aluminum
Color	<b>RAL 9016 (white)</b>
Diffuser	transparent polycarbonate
Impact resistant	IK04
Weight [kg]	0,25
Dimensions [mm]	75 x 50 x 148



# A graph of light

