

**Product:** BERYL KN DUO LED UP&DOWN 4x1,7W 24° E IP65 25 840

**Index:** 19.4242.1121.25



## Description

Luminary adapted to be mounted on walls. High lighting efficiency LEDs were used as light sources. Optical system consists of professional lens that provide light distribution of 5-21° angle. Owing to the optical system solutions, the product is highly effective. Its body is made from anodized aluminum profile. It is resistant to solids, dust, and liquids penetration – IP40 or IP65. This type of luminary is recommended for decorative or accent illumination, e.g. in restaurants, pubs, or cafes.

## Product information


Category	Architectural luminaires
Family	BERYL KN DUO LED UP&DOWN
Name	BERYL KN DUO LED UP&DOWN 4x1,7W 24° E IP65 25 840
Index	19.4242.1121.25
EAN	5902107241513



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	608
LED power [W]	7
Luminaire luminous flux [lm]	587
Power of luminaire [W]	8
Luminaire's light efficiency [lm/W]	73,4
Color of the light [K]	4000
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 36° / 36°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-20 ÷ 30
Driver	standard on/off (E)
Circuit load capacity	40 (B10), 78 (B16), 132 (C10), 158 (C16)

## Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK04
Weight [kg]	0,51
Dimensions [mm]	150 x 82 x 50

## A graph of light

