

Product: BERYL KN DUO LED UP&DOWN 4x1,7W 5°-21° E IP65 25 840

Index: 19.4242.2121.25



Description

Luminary adapted to be mounted on walls. High lighting efficiency LEDs were used as light sources. Optical system consists of professional lens that provide light distribution of 5-21° angle. Owing to the optical system solutions, the product is highly effective. Its body is made from anodized aluminum profile. It is resistant to solids, dust, and liquids penetration – IP40 or IP65. This type of luminary is recommended for decorative or accent illumination, e.g. in restaurants, pubs, or cafes.

Product information

Category	Architectural luminaires
Family	BERYL KN DUO LED UP&DOWN
Name	BERYL KN DUO LED UP&DOWN 4x1,7W 5°-21° E IP65 25 840
Index	19.4242.2121.25
EAN	5902107241476



Light and electrical data

Light source	LED
Luminous flux LED [lm]	608
LED power [W]	7
Luminaire luminous flux [lm]	489
Power of luminaire [W]	8
Luminaire's light efficiency [lm/W]	61,1
Color of the light [K]	4000
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 36° / 9,6°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L70/B50
Operating temperature range [°C]	-20 ÷ 30
Driver	standard on/off (E)
Circuit load capacity	40 (B10), 78 (B16), 132 (C10), 158 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	transparent polycarbonate
Impact resistant	IK04
Weight [kg]	0,51
Dimensions [mm]	150 x 82 x 50

A graph of light

