

Product: RUBIN LOOK LED SMOOTH COMPACT 4000 MICRO-PRM E 34 840

Index: 19.4250.2321.34



## **Description**

Surface mounted luminary for LED sources. Luminary body made from steel sheet, powder coated. Luminary recommended for: wards and hospital bathrooms.

#### **Product information**

Category	Compact	
Family	<b>RUBIN LOOK LED</b>	SMOOTH COMPACT
Name	<b>RUBIN LOOK LED</b>	SMOOTH COMPACT 4000 MICRO-PRM E 34 840
Index	19.4250.2321.34	
EAN	5902107184070	
















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	4695
LED power [W]	21,4
Luminaire luminous flux [lm]	3762
Power of luminaire [W]	28,9
Luminaire's light efficiency [lm/W]	130,2
Color of the light [K]	4000
CRI	>80
Beam angle [°]	(C0-C180) / (C90-C270) - 95,2° / 94,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection against electric shock Protection degree	I IP40
	•
Protection degree	IP40
Protection degree Voltage	IP40 220240 V, 5060 Hz
Protection degree  Voltage  Lifetime of LED sources [h]	IP40 220240 V, 5060 Hz 100000 (1) / 80000 (2)
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	IP40 220240 V, 5060 Hz 100000 (1) / 80000 (2) L70/B10 (1) / L80/B10 (2)
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	IP40 220240 V, 5060 Hz 100000 (1) / 80000 (2) L70/B10 (1) / L80/B10 (2) 5 ÷ 30

#### Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	2,2
Dimensions [mm]	365 x 365 x 50



# A graph of light

