

Product: X-WALL K9 LED COMPACT 2000 PLX E IP44 24 830 / L-575MM

Index: 19.4254.1111.24



Description

Surface mounted and wall luminaire. Luminaire body made from aluminum profile, its diffuser made from plastic. Its asymmetric optical system together with the diffuser provides high energetic efficiency. Luminaire recommended for: hospital bathrooms and wards.

Product information

Category	Compact
Family	X-WALL K9 LED COMPACT
Name	X-WALL K9 LED COMPACT 2000 PLX E IP44 24 830 / L-575MM
Index	19.4254.1111.24
EAN	5902107209865



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1994
LED power [W]	12
Luminaire luminous flux [lm]	1302
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	93
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-47°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,06
Dimensions [mm]	575 x 50 x 60

A graph of light

