

Product: X-WALL K9 LED COMPACT 2000 PLX E IP44 24 830 / L-575MM

Index: 19.4254.1111.24



Description

Wall mounted luminaire. Luminaire body made from aluminum profile, its diffuser made from plastic. Its asymmetric optical system together with the diffuser provides high energetic efficiency. Luminaire recommended for: hospital bathrooms and wards.

Product information


Category	Compact
Family	X-WALL K9 LED COMPACT
Name	X-WALL K9 LED COMPACT 2000 PLX E IP44 24 830 / L-575MM
Index	19.4254.1111.24
EAN	5902107209865



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1994
LED power [W]	12
Luminaire luminous flux [lm]	1302
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	93
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - $I_{max}=47^\circ$
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,06
Dimensions [mm]	575 x 50 x 60

A graph of light

