

Product: AGAT LED 6500 MICRO-PRM EDD 840 / 600X600

Index: 19.4257.3423.34



Description

Luminaire dedicated for module and suspended ceilings with the T24 grid, equipped with the highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Monolithic construction is the characteristic feature of the luminaire (remaining in one-piece during exploitation process). Luminaire available in PLX or Micro-PRM diffuser. Luminaire dedicated for the public use structure.

Product information

Category	Recessed luminaires
Family	AGAT LED
Name	AGAT LED 6500 MICRO-PRM EDD 840 / 600X600
Index	19.4257.3423.34



Light and electrical data


Light source	LED
Luminous flux LED [lm]	6543
LED power [W]	33,3
Luminaire luminous flux [lm]	5558
Power of luminaire [W]	34,8
Luminaire's light efficiency [lm/W]	159,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	5,6
Dimensions [mm]	596 x 596 x 90

A graph of light



Accessories

Index 2C1A7392-34R

Name EUROPANEL / BACKPANEL / RIM
COMPACT LED RECESSED
ACCESSORIES 34 / 600X600

