

Product: AGAT LED 11000 PLX E 34 840 / 600X600

Index: 19.4258.4421.34



Description

Luminaire dedicated for module and suspended ceilings with the T24 grid, equipped with the highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Monolithic construction is the characteristic feature of the luminaire (remaining in one-piece during exploitation process). Luminaire available in PLX or Micro-PRM diffuser. Luminaire dedicated for the public use structure.

Product information

Category	Recessed luminaires
Family	AGAT LED
Name	AGAT LED 11000 PLX E 34 840 / 600X600
Index	19.4258.4421.34
EAN	5902023888960



Light and electrical data

Light source	LED
Luminous flux LED [lm]	11689
LED power [W]	54,5
Luminaire luminous flux [lm]	9480
Power of luminaire [W]	61
Luminaire's light efficiency [lm/W]	155,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 105,8° / 106,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20/44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	5,5
Dimensions [mm]	596 x 596 x 90

A graph of light



Accessories

Index 2C1A7392-34R

Name EUROPANEL / BACKPANEL / RIM
COMPACT LED RECESSED
ACCESSORIES 34 / 600X600

