

**Product: AGAT LED 8800 PLX E 34 840 / 1200X300** 

Index: 19.4258.6321.34



## **Description**

Luminary dedicated for module and suspended ceilings with the T24 grid, equipped with the highly efficient LED sources. Luminary body made from steel sheet, powder coated in white. Monolithic construction is the characteristic feature of the luminary (remaining in one-piece during exploitation process). Luminary available in PLX or Micro-PRM diffuser. Luminary dedicated for the public use structure.

## **Product information**

Category	Recessed luminaires
Family	AGAT LED
Name	AGAT LED 8800 PLX E 34 840 / 1200X300
Index	19.4258.6321.34
EAN	5902023888496















## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	9351	
LED power [W]	43,6	
Luminaire luminous flux [lm]	7584	
Power of luminaire [W]	48,8	
Luminaire's light efficiency [lm/W]	155,4	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 105,8° / 106,2°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP20/44	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	



Mechanical data	Assembly	mounted in module ceilings
	Material	steel sheet
	Color	RAL 9016 (white)
B B	Diffuser	PLX (PMMA opal)
ŢH	Impact resistant	IK04
Α	Weight [kg]	4,2
	Dimensions [mm]	1196 x 296 x 90

## A graph of light

