


Product: BACKPANEL LED 5800 MICRO-PRM E IP20/44 34 830 600X600 Index: 19.4260.1311.34



Description

Modern LED panel dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using adaptive frame) or using adaptive frame and suspensions. Equipped with the highly efficient LED sources. Direct light distribution. Luminary body made from steel sheet. PMMA opal diffuser. Colour of luminary - white. CRI>80. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

Product	inform	ation
FIGUUCI		auon

	Category	Recessed luminaires			
	Family	BACKPANEL LED			
	Name BACKPANEL LED 5800 MICRO-PRM E IP20/44 34 830 600X600 Index 19.4260.1311.34				
	EAN	2107293802			
		$\underbrace{}_{\text{LED}} \underbrace{}_{\text{ED}} \underbrace{\square} \underbrace{_{\text{P20}}}_{\text{P44}} \underbrace{\coprod}_{\text{K}_{4}} \underbrace{}_{\text{index}} \underbrace{}_{\text{index}}$			

Light and electrical data


Light source	LED
Luminous flux LED [lm]	5538
LED power [W]	28,4
Luminaire luminous flux [lm]	4873
Power of luminaire [W]	31,8
Luminaire's light efficiency [lm/W]	153,2
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,6° / 93°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	29 (B10), 46 (B16), 46 (C10), 74 (C16)



Mechanical data	Assembly	mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories
В	Material	steel sheet
	th Color	RAL 9016 (white)
	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
la	Impact resi	stant IK04
	Weight [kg]	3,1
	Dimensions	s [mm] 596 x 596 x 34
A graph of light		$105^{\circ} \\ 105^{\circ} \\ 105^$



Accessories




Index 19.3213.0083.34

Name BACKPANEL LED SURFACE ACCESSORIES BASIC 34 / 600X600





Name BACKPANEL LED SURFACE ACCESSORIES 34 / 600X600




Index 19.3213.0076.34

Name BACKPANEL LED / RIM LED

ACCESSORIES SET WITH

SUSPENSION 1,5M / 600X600



Index 19.3213.0082.34

Name BACKPANEL COMPACT LED

NASTROPOWA RAMKA

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025