


Product: BACKPANEL LED 3800 PLX EDD IP20/44 34 830 600X600 Index: 19.4260.3113.34



Description

Modern LED panel dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using adaptive frame) or using adaptive frame and suspensions. Equipped with the highly efficient LED sources. Direct light distribution. Luminary body made from steel sheet. PMMA opal diffuser. Colour of luminary - white. CRI>80. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

Produc	t inform	lation

Category	Recessed luminaires	
Family	BACKPANEL LED	
Name	BACKPANEL LED 3800 PLX EDD IP20/44 34 830 600X600	
Index	19.4260.3113.34	
EAN	5902107293628	
	$\underbrace{}_{\text{LED}} \underbrace{}_{\text{ED}} \underbrace{\square} \underbrace{\overset{\text{IP20}}{\text{IP44}}}_{\text{IP44}} \underbrace{\overset{\text{IV}}{\text{IV}}}_{\text{IP40}} \underbrace{}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}}_{\text{IP40}} \underbrace{}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}}_{\text{IP40}} \underbrace{\overset{\text{IV}}{\text{IP40}}}_{\text{IP40}} \overset$	


Light and electrical data

Light source	LED
Luminous flux LED [lm]	3728
LED power [W]	18,4
Luminaire luminous flux [lm]	3355
Power of luminaire [W]	20,6
Luminaire's light efficiency [lm/W]	162,8
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,8° / 114,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	20 (B10), 30 (B16), 32 (C10), 52 (C16)




Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories B Material steel sheet Color RAL 9016 (white) Ţн Diffuser PLX (PMMA opal) Impact resistant IK04 Dimensions [mm] 596 x 596 x 34

A graph of light





Accessories




Index 19.3213.0083.34

Name BACKPANEL LED SURFACE ACCESSORIES BASIC 34 / 600X600





Name BACKPANEL LED SURFACE ACCESSORIES 34 / 600X600




Index 19.3213.0076.34

Name BACKPANEL LED / RIM LED

ACCESSORIES SET WITH

SUSPENSION 1,5M / 600X600



Index 19.3213.0082.34

Name BACKPANEL COMPACT LED

NASTROPOWA RAMKA

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025