

Product: ARUNA LED 1R 2600 OPTICS-1L E 34 840 / 1200X300 Index: 19.4261.4321.34




Description

LED luminary dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using ceiling slab) or using slings. Equipped with highly efficient LED light sources. Light distribution available with modern lenses. Housing made of steel sheet. Standard colour of the luminary is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80. Thanks to its innovative optics Aruna LED perfectly fits to be used in offices-especially to work with computers.

Product information Category Recessed luminaires Family ARUNA LED Name ARUNA LED Name ARUNA LED Name ARUNA LED Light and electrical data Light source Light and electric sources So Protection against electric shock I Pr						
Family ARUNA LED Name ARUNA LED 1R 2600 OPTICS-1L E 34 840 / 1200X300 Index 134261.4321.34 EAN 5902107190392 Image: Second Se	Product information	Category Recessed lum	Category Recessed luminaires			
Index 19.4261.4321.34 EAN 5902107190392 Image: Construction of the state of the stat			Family ARUNA LED			
EAN 5902107190392 Image: Second Se		Name ARUNA LED 1				
Light and electrical data Light source LED Luminous flux LED [lm] 2617 LED power (M) 13,3 Luminaire luminous flux (Im) 2089 Power of luminaire [M] 14,4 Luminaire's light efficiency [lmM] 145,1 Color of the light [K] 4000 CR >80 SDCM (LED sources) 3 Beam angle ['] (Co-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220.240 V, 50.60 Hz Lifetime of LED sources [h] 100000 LVBy L70IB50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Material steel sheet A Diffuser Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9						
Light and electrical data Light source LED Luminous flux LED [Im] 2617 LED power [M] 13,3 Luminaire luminous flux [Im] 2099 Power of luminaire [M] 14,4 Luminaire's light efficiency [Im/M] 145,1 Color of the light [K] 4000 CRI >800 SDCM (LED sources) 3 Beam angle ['] (C0-C1380) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED Sources [h] 100000 LX/By Clean cos q 20940 K, 33 (C10), 54 (C16) Driver standard on/off (E) Power factor cos q 20.95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical dataH Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [K] 5,9 Dimensions [mm] 1193 x 293 x 39		EAN 590210719039	2			
A Luminous flux LED [Im] 2617 LED power [W] 13,3 Luminaire luminous flux [Im] 2089 Power of luminaire [Vm] 14,4 Luminaire's light efficiency [Im/W] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220,240 V; 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos qo >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses)		CE	$\square \square $			
A Luminous flux LED [Im] 2617 LED power [W] 13,3 Luminaire luminous flux [Im] 2089 Power of luminaire [Vm] 14,4 Luminaire's light efficiency [Im/W] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220,240 V; 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos qo >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses)	Light and electrical data	Light source	LED			
Luminaire luminous flux [lm] 2089 Power of luminaire [W] 14,4 Luminaire's light efficiency [lm/W] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock 1 Protection degree IP20 Voltage 220.240 V, 50.60 Hz Lifetime of LED sources [h] 100000 Lx/By L70/IS50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on siting using accessories A Solid Corr RAL 9016 (white) Diffuser Diffuser Ford cresistant IK04 Weight [Kg] 5,9 Dimensions [mm] 1193 x 293 x 39		Luminous flux LED [Im]	2617			
Luminaire luminous flux [lm] 2089 Power of luminaire [W] 14,4 Luminaire's light efficiency [lm/W] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock 1 Protection degree IP20 Voltage 220.240 V, 50.60 Hz Lifetime of LED sources [h] 100000 Lx/By L70/IS50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on siting using accessories A Solid Corr RAL 9016 (white) Diffuser Diffuser Ford cresistant IK04 Weight [Kg] 5,9 Dimensions [mm] 1193 x 293 x 39		LED power [W]	13,3			
Power of luminaire [M] 14,4 Luminaire's light efficiency [Im/M] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle ["] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 LiXBy L70/B50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceilings construction and surface mounted on silings using accessories						
Luminaire's light efficiency [Im/W] 145,1 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 + 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Material steel sheet Color RAL 9016 (white) Diffuser OPTCS (optical system based on lenses) Impact resistant IK04 Weight [Kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings, directly mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color Color RAL 9016 (white) Diffuser Diffuser OPTICS (optical system based on lenses) Impact resistant Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 × 293 × 39 3						
SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos ϕ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color Color RAL 9016 (white) Diffuser Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 × 293 × 39						
Beam angle ['] (C0-C180) / (C90-C270) - 100,4° / 90,8° Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Protection against electric shock I Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39		. , ,				
Protection degree IP20 Voltage 220240 V, 5060 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Voltage 220.240 V, 50.60 Hz Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Lifetime of LED sources [h] 100000 Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39			220240 V, 5060 Hz			
Lx/By L70/B50 Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Operating temperature range [°C] 5 ÷ 30 Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39			L70/B50			
Driver standard on/off (E) Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39		-	ie [°C] 5 ÷ 30			
Power factor cos φ >0,95 Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Circuit load capacity 22 (B10), 34 (B16), 33 (C10), 54 (C16) Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories Material Steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Mechanical data Assembly mounted in module ceilings as well as plasterboard ceilings, directly mounted to ceiling construction and surface mounted on slings using accessories A Material steel sheet Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39		· · · · ·				
A Slings using accessories A A A Color Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39	Mechanical data	plasterboard ceilings, directly mounted to				
B Material steel sheet A Color RAL 9016 (white) Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
A Color RAL 9016 (white) A Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39		Material				
A Diffuser OPTICS (optical system based on lenses) Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Impact resistant IK04 Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Weight [kg] 5,9 Dimensions [mm] 1193 x 293 x 39						
Dimensions [mm] 1193 x 293 x 39						
		Mounting hole [mm]	1210 x 310			

A graph of light



Accessories

Index	19.3044.0001.34			

Name Frame for ceiling mounting / 1200X300



Index 01ARNL-AGK120X30 Name Adaptive frame for plasterboard ceiling / 1200X300



Index 19.3272.0101.34

Name SUSPENSION NEW TYPE-G+H 34 LENGHT 1,5M WIRE 3X SET TYPE-Y



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025