

Product: ARUNA LED 1R 4000 OPTICS-1L E 34 840 / 600X300

Index: 19.4261.1521.34



Description

LED luminaire dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using ceiling slab) or using slings. Equipped with highly efficient LED light sources. Light distribution available with modern lenses. Housing made of steel sheet. Standard colour of the luminaire is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80. Thanks to its innovative optics Aruna LED perfectly fits to be used in offices-especially to work with computers.

Product information


| | |
|----------|--|
| Category | Recessed luminaires |
| Family | ARUNA LED |
| Name | ARUNA LED 1R 4000 OPTICS-1L E 34 840 / 600X300 |
| Index | 19.4261.1521.34 |
| EAN | 5902107193478 |



Light and electrical data


| | |
|-------------------------------------|---|
| Light source | LED |
| Luminous flux LED [lm] | 4165 |
| LED power [W] | 26 |
| Luminaire luminous flux [lm] | 3325 |
| Power of luminaire [W] | 29 |
| Luminaire's light efficiency [lm/W] | 114,7 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 100,4° / 90,8° |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 (1) / 147000 (2) |
| Lx/By | L80/B10 (1) / L70/B50 (2) |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 15 (B10), 24 (B16), 24 (C10), 40 (C16) |

Mechanical data



| | |
|--------------------|--|
| Assembly | mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted on slings (using accessories) |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | OPTICS (optical system based on lenses) |
| Impact resistant | IK04 |
| Dimensions [mm] | 593 x 293 x 39 |
| Mounting hole [mm] | 610 x 310 |

A graph of light



Accessories

Index 19.3272.0101.34
Name SUSPENSION NEW TYPE-G+H
34 LENGHT 1,5M WIRE 3X SET
TYPE-Y



Index 2C1A8939
Name Adaptive frame for plasterboard
ceiling / 600X300

