

Product: ARUNA LED 2R 2600 OPTICS-1L E 34 840 / 600X300

Index: 19.4261.2321.34



Description

LED luminaire dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using ceiling slab) or using slings. Equipped with highly efficient LED light sources. Light distribution available with modern lenses. Housing made of steel sheet. Standard colour of the luminaire is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80. Thanks to its innovative optics Aruna LED perfectly fits to be used in offices-especially to work with computers.

Product information


Category	Recessed luminaires
Family	ARUNA LED
Name	ARUNA LED 2R 2600 OPTICS-1L E 34 840 / 600X300
Index	19.4261.2321.34
EAN	5902107193423



Light and electrical data


Light source	LED
Luminous flux LED [lm]	2617
LED power [W]	13,3
Luminaire luminous flux [lm]	2089
Power of luminaire [W]	14,4
Luminaire's light efficiency [lm/W]	145,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 100,4° / 90,8°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L70/B50
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data




Assembly	mounted in module ceilings, plasterboard ceilings (using accessories) or surface mounted on slings (using accessories)
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	OPTICS (optical system based on lenses)
Impact resistant	IK04
Dimensions [mm]	593 x 293 x 39
Mounting hole [mm]	610 x 310

A graph of light



Accessories

Index 19.3272.0101.34
Name SUSPENSION NEW TYPE-G+H
34 LENGHT 1,5M WIRE 3X SET
TYPE-Y



Index 2C1A8939
Name Adaptive frame for plasterboard ceiling / 600X300

