

Product: AMETYST NEW LED 4000 PC E MWS IP65 34 840

Index: 19.4271.1428.34



Description

Surface mounted or wall luminary equipped in highly efficient LED panels. Luminary body and diffuser made from IK10 impact resistant material. Luminary recommended for: bathrooms, wards, medical staff room and also in outdoor areas. The product is equipped with a microwave motion sensor.

Product information

Category	Surface mounted luminaires
Family	AMETYST NEW LED
Name	AMETYST NEW LED 4000 PC E MWS IP65 34 840
Index	19.4271.1428.34
EAN	5902107152390













Light and electrical data

Light source	LED
Luminous flux LED [lm]	4103
LED power [W]	23
Luminaire luminous flux [lm]	3230
Power of luminaire [W]	25,8
Luminaire's light efficiency [lm/W]	125,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 112,6° / 112,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 80000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	-20 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	39 (B10), 62 (B16), 65 (C10), 104 (C16)



Mechanical data





Assembly	surface mounted on ceiling or on wall
Material	polycarbonate
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Weight [kg]	1,23
Dimensions [mm]	Ø356 x 76

A graph of light



