

В

Product: AGALINE LED 3R 21600 OPTICS-1 EDD 34 IP65 840 / L-1860MM Index: 19.4200.4123.34



Description

Agaline 3R is a single linear luminaire designed for mounting on slings. The body is made of white powder-coated steel sheet. Optical system based on lenses providing different light distribution. High level of protection against penetration of dust and water - IP65. Agaline is an excellent solution for lighting industrial facilities and warehouses, but also finds application in offices, supermarkets and shops.

| Product information | Category Industrial luminaires | | |
|---------------------------|---|--|--|
| | Family AGALINE LED 3R | FamilyAGALINE LED 3RNameAGALINE LED 3R 21600 OPTICS-1 EDD 34 IP65 840 / L-1860MMIndex19.4200.4123.34 | |
| | Name AGALINE LED 3R 21600 OPTI | | |
| | Index 19.4200.4123.34 | | |
| | EAN 5902107252588 | | |
| | | | |
| Light and electrical data | Light source | LED | |
| | Luminous flux LED [lm] | 24012 | |
| | LED power [W] | 129,6 | |
| | Luminaire luminous flux [lm] | 22811,4 | |
| | Power of luminaire [W] | 145,2 | |
| | Luminaire's light efficiency [lm/W] | 157,1 | |
| | Color of the light [K] | 4000 | |
| | CRI | >80 | |
| | SDCM (LED sources) | 3 | |
| | | (C0-C180) / (C90-C270) - 68,2° / 69,4° | |
| | Photobiological risk class (IEC/EN 62471) | RG0 | |
| | Protection against electric shock | I | |
| | Protection degree | IP65 | |
| | Voltage | 220240 V, 5060 Hz | |
| | Lifetime of LED sources [h] | 90000 | |
| | Lx/By | L80B10 | |
| | Operating temperature range [°C] | -25 ÷ 35 | |
| | Driver | DIM DALI (EDD) | |
| Mechanical data | Assembly surface n | Assembly surface mounted on slings Material steel sheet | |
| | Material steel she | | |
| | Color RAL 9016 | Color RAL 9016 (white) | |
| A | Diffuser OPTICS (| | |
| | Impact resistant IK04 | - | |
| | Dimensions [mm] 1860 x 95 | 5 x 68 | |

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025








Accessories


- Index 6E1-500KW34K-5
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET



- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT







ME SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-5
 - Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 5X SET



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025