

В

## Product: AGALINE LED 3R 21600 OPTICS-2 E 34 IP65 830 / L-1860MM Index: 19.4200.4211.34



## Description

Agaline 3R is a single linear luminaire designed for mounting on slings. The body is made of white powder-coated steel sheet. Optical system based on lenses providing different light distribution. High level of protection against penetration of dust and water - IP65. Agaline is an excellent solution for lighting industrial facilities and warehouses, but also finds application in offices, supermarkets and shops.

| Product information       | Category Industrial luminaires            |   |  |
|---------------------------|---|---|--|
|                           | Family AGALINE LED 3R                     |   |  |
|                           | Name AGALINE LED 3R 21600                 | Name AGALINE LED 3R 21600 OPTICS-2 E 34 IP65 830 / L-1860MM |  |
|                           | Index 19.4200.4211.34                     |   |  |
|                           | EAN 5902107428341                         |   |  |
|                           |   | $\textcircled{P} \bigoplus P_{65} \swarrow $                |  |
| Light and electrical data | Light source                              | LED   |  |
|                           | Luminous flux LED [lm]                    | 22884   |  |
|                           | LED power [W]                             | 129,6   |  |
|                           | Luminaire luminous flux [lm]              | 21739,8   |  |
|                           | Power of luminaire [W]                    | 145,2   |  |
|                           | Luminaire's light efficiency [lm/W]       | 149,7   |  |
|                           | Color of the light [K]                    | 3000  |  |
|                           | CRI                                       | >80   |  |
|                           | SDCM (LED sources)                        | 3   |  |
|                           | Beam angle [°]                            | (C0-C180) / (C90-C270) - 43,6° /<br>83,2°                   |  |
|                           | Photobiological risk class (IEC/EN 62471) | RG0   |  |
|                           | Protection against electric shock         | I   |  |
|                           | Protection degree                         | IP65  |  |
|                           | Voltage                                   | 220240 V, 5060 Hz   |  |
|                           | Lifetime of LED sources [h]               | 90000   |  |
|                           | Lx/By                                     | L80B10  |  |
|                           | Operating temperature range [°C]          | -25 ÷ 35  |  |
|                           | Driver                                    | standard on/off (E)   |  |
| Mechanical data           | Assembly surfa                            | ace mounted on slings                                       |  |
|                           | Material stee                             | sheet   |  |
| A                         | Color RAL                                 | 9016 (white)  |  |
|                           |   | CS (optical system based on lenses)                         |  |
|                           | Impact resistant IK04                     |   |  |
| H <u></u>                 |   | x 95 x 68   |  |









## Accessories


- Index 6E1-500KW34K-3
- Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




- Index 6E1-9875-4-1,5-3X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT







Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

Index 19.3272.1205.00

- Index 6E1-500KWB34K-3
- Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET



