


Product: ATENA LINE NEW OUTDOOR RECESSED LED 24000 SH NARROW E IP65 04 850 / KRATA

Index: 19.4203.3461.04



# **Description**

Industrial luminaire dedicated to be mounted in suspended ceiling/board with a thickness of 10 to 50 mm. The external application is possible due to the fact that the product is equipped with a pressure compensation valve, and the housing has a special painting adapted to the external conditions. Rectangular housing made of aluminum sheet. Anodized profile to increase the corrosion resistance of the luminaire. Only one colour available: RAL 9005 (black). Upon client request there is a possibility to make longer luminaire than standard dimensions. Consequently, the luminaire will have bigger luminous flux. The light sources are protected by diffuser made of hartened glass and the whole construction is characterized by high level of protection against dust and water penetration-IP65.

#### **Product information**

Category	Outdoor luminaires
Family	ATENA LINE NEW OUTDOOR RECESSED LED
Name	ATENA LINE NEW OUTDOOR RECESSED LED 24000 SH NARROW E IP65 04 850 / KRATA
Index	19.4203.3461.04
EAN	5902107288655














## Light and electrical data

LED
25213
135
19422
138
140,7
5000
>80
3
(C0-C180) / (C90-C270) - 21,8° / 22°
I
IP65
220240 V, 5060 Hz
83000
L90/B10
-25 ÷ 40
standard on/off (E)
>0,95
14 (B10), 22 (B16), 14 (C10), 22 (C16)

### Mechanical data



Assembly	mounted in suspended ceiling/board
Material	aluminum
Color	RAL 9005 (black)
Diffuser	SH (transparent hardened glass)
Impact resistant	IK08
Weight [kg]	9,32
Dimensions [mm]	616 x 250 x 200



# A graph of light

