

**Product:** PRISON LED 10400 PC E 34 IP65 840 / 1240X200MM

**Index:** 19.4204.5421.34



## Description

Surface mounted LED luminaire. Luminaire body made from steel sheet, powder coated in white. Luminaire 40 J impact resistant. Luminaire recommended for rooms of vandal and humidity hazards.

## Product information

Category	Industrial luminaires
Family	PRISON LED
Name	PRISON LED 10400 PC E 34 IP65 840 / 1240X200MM
Index	19.4204.5421.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	10468
LED power [W]	53,2
Luminaire luminous flux [lm]	7879
Power of luminaire [W]	56,3
Luminaire's light efficiency [lm/W]	139,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106,6° / 106,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Weight [kg]	8,8
Dimensions [mm]	1240 x 200 x 60

## A graph of light

