

Product: PRISON LED 2600 PC EDD IP65 34 840 / 650X325MM

Index: 19.4204.1223.34



Description

Surface mounted LED luminary. Luminary body made from steel sheet, powder coated in white. Luminary 40 J impact resistant. Luminary recommended for rooms of vandal and humidity hazards.

Product information

Category	Industrial luminaires
Family	PRISON LED
Name	PRISON LED 2600 PC EDD IP65 34 840 / 650X325MM
Index	19.4204.1223.34
EAN	5902107221119














Light and electrical data

Light source	LED
Luminous flux LED [lm]	2617
LED power [W]	13,3
Luminaire luminous flux [lm]	1970
Power of luminaire [W]	14,4
Luminaire's light efficiency [lm/W]	136,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 106,6° / 106,2°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Dimensions [mm]	650 x 325 x 60



A graph of light

