

Product: RUBIN INDUSTRY SLIGHT LED 24000 OPTICS-2L PC-T IP65 E 34 840 / 1270X320MM HT45

Index: 19.4205.1321.34



Description

Luminary dedicated for big space industry areas. ceiling mounting. Light distribution made by using high performance lenses. Luminary body made from steel sheet, powder coated in white. The product is recommended for production halls, warehouses and heavy industry.

Product information

Category	Industrial luminaires
Family	RUBIN INDUSTRY SLIGHT LED
Name	RUBIN INDUSTRY SLIGHT LED 24000 OPTICS-2L PC-T IP65 E 34 840 / 1270X320MM HT45
Index	19.4205.1321.34
EAN	5902107207120
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	24990
LED power [W]	153
Luminaire luminous flux [lm]	19975
Power of luminaire [W]	171
Luminaire's light efficiency [lm/W]	116,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 56,4° / 92,6°
Protection against electric shock	1
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 45
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 22 (B16), 14 (C10), 22 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PC-T (transparent polycarbonate)
Impact resistant	IK08
Weight [kg]	9
Dimensions [mm]	1270 x 320 x 55



A graph of light

