

## Product: RUBIN SPORT NEW LED 32000 MICRO-PRM KR E 34 830 / 1190X320MM Index: 19.4206.4111.34




## Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Product information	Category Industrial luminaires
	Family RUBIN SPORT NEW LED
	Name RUBIN SPORT NEW LED 32000 MICRO-PRM KR E 34 830 / 1190X320MM
	Index 19.4206.4111.34
	EAN 5902107181963
Light and electrical data	Light source LED
	Luminous flux LED [Im] 33056
	LED power [W] 164,8
	Luminaire luminous flux [Im] 24824,2
	Power of luminaire [W] 184,6
	Luminaire's light efficiency [lm/W] 134,5
	Color of the light [K] 3000
	CRI >80
	SDCM (LED sources) 3
	Beam angle [°] (C0-C180) / (C90-C270) - 90,2° / 99,6
	Protection against electric shock
	Protection degree IP20
	Voltage 220240 V, 5060 Hz
	Lifetime of LED sources [h] 100000 (1) / 147000 (2)
	Lx/By L80/B10 (1) / L70/B50 (2)
	Operating temperature range [°C] 5 ÷ 30
	Driver standard on/off (E)
	Power factor cos φ >0,95
	Circuit load capacity 7 (B10), 11 (B16), 7 (C10), 11 (C16)
Mechanical data	Assembly surface mounted on ceiling
	Material steel sheet
	Color RAL 9016 (white)
	Diffuser Micro-PRM (micro-prismatic diffuser PMM
	TH Impact resistant IK10
A	Dimensions [mm] <b>1190 x 320 x 60</b>

## A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 09-09-2025