

Product: RUBIN SPORT NEW LED 24000 MICRO-PRM KR E 34 840 / 1190X320MM Index: 19.4206.3121.34




Description

Surface mounted luminary dedicated for the sports, gymnastics and squash halls, etc. Luminary equipped with the protecting grid made from steel wire powder coated. Diffuser used in the luminary provides less glare effect for the room users when compared to the light sources used in the fluorescents.

Due due tinfermentier		
Product information	Category Industrial luminaires	
	Family RUBIN SPORT NEW LED	
	Name RUBIN SPORT NEW LED 24000 MICRO-PRM KR E 34 840 1190X320MM	1
	Index 19.4206.3121.34	
	EAN 5902107187637	
		A Nor
Light and electrical data	Light source LED	
	Luminous flux LED [lm] 26094	
	LED power [W] 123,6	
	Luminaire luminous flux [Im] 19595,9	
	Power of luminaire [W] 138,4	
	Luminaire's light efficiency [lm/W] 141,6	
	Color of the light [K] 4000	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] (C0-C180) / (C90-C270) - 90,2° /	99,6°
	Protection against electric shock	
	Protection degree IP20	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 100000 (1) / 147000 (2)	
	Lx/By L80/B10 (1) / L70/B50 (2)	
	Operating temperature range [°C] 5 ÷ 30	
	Driver standard on/off (E)	
	Power factor cos φ >0,95	
	Circuit load capacity 7 (B10), 11 (B16), 7 (C10), 11 (C	;16)
Mechanical data	Assembly surface mounted on ceiling	
	Material steel sheet	
	Color RAL 9016 (white)	
	Diffuser Micro-PRM (micro-prismatic diffuser	PMMA)
	H Impact resistant IK10	
	Weight [kg] 9,86	

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 09-09-2025