

## Product: RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG E 34 830 / 1190X220MM Index: 19.4207.1211.34



## Description


Surface mounted luminary dedicated for sports halls, gyms and schools. The body is made of powder-coated steel sheet. The luminary is equipped with a PC and PMMA diffuser (with a microprismatic structure) with an additional stiffening mount, which does not require a protective grid.

Product information	Cotogory Industrial luminaires	
	Category Industrial luminaires	
	Family RUBIN SPORT NEW LED	
	Name RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRO 34 830 / 1190X220MM	NGE
	Index 19.4207.1211.34	
	EAN 5902107260217	
	$\begin{array}{c} \hline \\ \hline $	Ŕ
Light and electrical data	Light source LED	
	Luminous flux LED [Im] 16528	
	LED power [W] 82,4	
	Luminaire luminous flux [lm] 11400,1	
	Power of luminaire [W] 92,3	
	Luminaire's light efficiency [lm/W] 123,5	
	Color of the light [K] 3000	
	CRI >80	
	SDCM (LED sources) 3	
	Beam angle [°] (C0-C180) / (C90-C270) - 90,2° / 99	,6°
	Protection against electric shock I	
	Protection degree IP44	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 100000 (1) / 147000 (2)	
	Lx/By L80/B10 (1) / L70/B50 (2)	
	Operating temperature range [°C] 5 ÷ 30	
	Driver standard on/off (E)	
	Power factor $\cos \phi$ >0,95	
	Circuit load capacity 14 (B10), 22 (B16), 14 (C10), 22 (C1	L6)
Mechanical data	Assembly surface mounted on ceiling	
В	Material steel sheet	
	Color RAL 9016 (white)	
	Diffuser PC-T MICRO-PRM (transparent polycarbor and micro-prismatic diffuser PMMA)	nate
	Impact resistant IK10	

Dimensions [mm]

1190 x 220 x 60

## A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 09-09-2025