

Product: RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG EDD 34 840 / 1190X220MM

Index: 19.4207.1223.34



Description

Surface mounted luminary dedicated for sports halls, gyms and schools. The body is made of powder-coated steel sheet. The luminary is equipped with a PC and PMMA diffuser (with a microprismatic structure) with an additional stiffening mount, which does not require a protective grid.

Product information

| Category Industrial luminaires | | |
|--------------------------------|--|--|
| Family | RUBIN SPORT NEW LED | |
| Name | RUBIN SPORT NEW LED 16000 PC-T MICRO-PRM IP44 STRONG EDD 34 840 / 1190X220MM | |
| Index | 19.4207.1223.34 | |
| EAN | 5902107260231 | |
















Light and electrical data

| Light source | LED |
|-------------------------------------|--|
| Luminous flux LED [lm] | 17396 |
| LED power [W] | 82,4 |
| Luminaire luminous flux [lm] | 11998,8 |
| Power of luminaire [W] | 92,3 |
| Luminaire's light efficiency [lm/W] | 130 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 90,2° / 99,6° |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 100000 (1) / 147000 (2) |
| Lx/By | L80/B10 (1) / L70/B50 (2) |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 18 (B10), 32 (B16), 18 (C10), 32 (C16) |

Mechanical data



| Assembly | surface mounted on ceiling |
|------------------|--|
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | PC-T MICRO-PRM (transparent polycarbonate and micro-prismatic diffuser PMMA) |
| Impact resistant | IK10 |
| Weight [kg] | 7,6 |
| Dimensions [mm] | 1190 x 220 x 60 |



A graph of light

