

Product: NEPTUN LED 4400 GRP OPAL E IP65 840 / L-1200 B1-GLUED/C3

Index: 19.4208.1321.00



Description

The luminaire housing made of polyester reinforced by fire-resistant glass fibre in light grey colour (RAL 7035). Application of this material ensures resistance to thermal, mechanical and chemical agents activity. Opalized diffuser is made of PMMA and is installed in luminaire body indelibly by using special adhesive sealant. This way of connection guarantees resistance against dust and water penetration to inside of the luminaire. The material which luminaire is made of and the way it is bonded ensures the resistance to chemical substances used in food industry.

Product information


Category	Industrial luminaires
Family	NEPTUN LED GRP
Name	NEPTUN LED 4400 GRP OPAL E IP65 840 / L-1200 B1-GLUED/C3
Index	19.4208.1321.00
EAN	5902107199661



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4565
LED power [W]	23,4
Luminaire luminous flux [lm]	3927
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	159
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 120,2° / 100,4°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polyester reinforced by fire-resistant glass fibre
Color	light grey (RAL7035)
Diffuser	PMMA opal
Impact resistant	IK10
Dimensions [mm]	1277 x 116 x 99

A graph of light

