

**Product:** NEPTUN LED 8800 GRP OPAL E IP65 840 / L-1200 B2-GLUED/C1

**Index:** 19.4208.2421.00



## Description

The luminaire housing made of polyester reinforced by fire-resistant glass fibre in light gray colour (RAL 7035). Application of this material ensures resistance to thermal, mechanical and chemical agents activity. Opalized diffusor is made of PMMA and is installed in luminaire body indelibly by using special adhesive sealant. This way of connection guarantees resistance against dust and water penetration to inside of the luminaire. The material which luminaire is made of and the way it is bonded ensures the resistance to chemical substances used in food industry.

## Product information


Category	<b>Industrial luminaires</b>
Family	<b>NEPTUN LED GRP</b>
Name	<b>NEPTUN LED 8800 GRP OPAL E IP65 840 / L-1200 B2-GLUED/C1</b>
Index	<b>19.4208.2421.00</b>
EAN	<b>5902107197964</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>9130</b>
LED power [W]	<b>46,8</b>
Luminaire luminous flux [lm]	<b>7854</b>
Power of luminaire [W]	<b>49,1</b>
Luminaire's light efficiency [lm/W]	<b>160</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 120,2° / 100,4°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP65</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000 (1) / 147000 (2)</b>
Lx/By	<b>L80/B10 (1) / L70/B50 (2)</b>
Operating temperature range [°C]	<b>-25 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>15 (B10), 25 (B16), 24 (C10), 38 (C16)</b>

**Mechanical data**



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polyester reinforced by fire-resistant glass fibre
Color	light grey (RAL7035)
Diffuser	PMMA opal
Impact resistant	IK10
Dimensions [mm]	1277 x 116 x 99

**A graph of light**

