

**Product:** AGALINE LED 8000 EDD 34 840 / L-1125MM

**Index:** 19.4210.2123.34



## Description

Agaline is an industrial modular system for installing in straight lines. Agaline is an excellent option for lighting industrial premises and warehouses, but is also suitable for offices, supermarkets and commercial spaces. A luminaire mounted in line systems, made of sheet steel, painted in white. Individual elements of the system combined with connectors. Through-cablings ensures easy and fast installation. To be applied in industrial objects and other places, where high intensity and uniformity of lighting is necessary. ATTENTION: Length 2805mm for special request.

## Product information

|          |   |
|----------|---|
| Category | <b>Industrial luminaires</b>                  |
| Family   | <b>AGALINE LED</b>                            |
| Name     | <b>AGALINE LED 8000 EDD 34 840 / L-1125MM</b> |
| Index    | <b>19.4210.2123.34</b>                        |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | <b>LED</b>                                      |
| Luminous flux LED [lm]                    | <b>8698</b>                                     |
| LED power [W]                             | <b>41,2</b>                                     |
| Luminaire luminous flux [lm]              | <b>8698</b>                                     |
| Power of luminaire [W]                    | <b>46,1</b>                                     |
| Luminaire's light efficiency [lm/W]       | <b>188,7</b>                                    |
| Color of the light [K]                    | <b>4000</b>                                     |
| CRI                                       | <b>&gt;80</b>                                   |
| SDCM (LED sources)                        | <b>3</b>  |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 114,4° / 114,4°</b> |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                      |
| Protection against electric shock         | <b>I</b>  |
| Protection degree                         | <b>IP20</b>                                     |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                    |
| Lifetime of LED sources [h]               | <b>100000</b>                                   |
| Lx/By                                     | <b>L80/B10</b>                                  |
| Operating temperature range [°C]          | <b>5 ÷ 35</b>                                   |
| Driver                                    | <b>DIM DALI (EDD)</b>                           |

## Mechanical data




|                  |                                  |
|------------------|----------------------------------|
| Assembly         | <b>surface mounted on slings</b> |
| Material         | <b>steel sheet</b>               |
| Color            | <b>RAL 9016 (white)</b>          |
| Diffuser         | <b>none</b>                      |
| Impact resistant | <b>IK04</b>                      |
| Dimensions [mm]  | <b>1125 x 56 x 45</b>            |



## Accessories


Index 0E1ALLS-SP

Name AGALINE LED CONNECTOR




Index 0E1ALLS-E

Name AGALINE LED END-CAP 34



Index 0E1ALLS-EP

Name AGALINE LED END-CAP 34  
Through wiring




Index 1E1AL8030-2-2

Name COVER 8030-2-2 RAL9016



Index 6E1-500KW34K-5

Name SUSPENSION NEW TYPE-A+B 34  
LENGHT 1,5M WIRE 5X SET




Index 6E1-8670-B-1,5-5X

Name SUSPENSION NEW TYPE-F  
LENGHT-1,5 METER WIRE 5X 1-  
POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT



Index 6E1-500KWB34K-5

Name SUSPENSION NEW TYPE-A+E 34  
LENGHT 1,5M WIRE 5X SET



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D  
LENGHT-1,5 METER WIRE 5X 1-  
POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT

