

**Product:** AGALINE LED 8000 ODB PLX E 34 830 / L-1125MM

**Index:** 19.4210.2311.34



## Description

Agaline is an industrial modular system for installing in straight lines. Agaline is an excellent option for lighting industrial premises and warehouses, but is also suitable for offices, supermarkets and commercial spaces. A luminaire mounted in line systems, made of sheet steel, painted in white. Individual elements of the system combined with connectors. Through-cabing ensures easy and fast installation. To be applied in industrial objects and other places, where high intensity and uniformity of lighting is necessary. ATTENTION: Lenght 2805mm for special request.

## Product information


|          |                                                     |
|----------|-----------------------------------------------------|
| Category | <b>Industrial luminaires</b>                        |
| Family   | <b>AGALINE LED</b>                                  |
| Name     | <b>AGALINE LED 8000 ODB PLX E 34 830 / L-1125MM</b> |
| Index    | <b>19.4210.2311.34</b>                              |
| EAN      | <b>5902107428679</b>                                |



## Light and electrical data

|                                           |                                                 |
|-------------------------------------------|-------------------------------------------------|
| Light source                              | <b>LED</b>                                      |
| Luminous flux LED [lm]                    | <b>8264</b>                                     |
| LED power [W]                             | <b>41,2</b>                                     |
| Luminaire luminous flux [lm]              | <b>6693,8</b>                                   |
| Power of luminaire [W]                    | <b>46,1</b>                                     |
| Luminaire's light efficiency [lm/W]       | <b>145,2</b>                                    |
| Color of the light [K]                    | <b>3000</b>                                     |
| CRI                                       | <b>&gt;80</b>                                   |
| SDCM (LED sources)                        | <b>3</b>                                        |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 108,6° / 109,4°</b> |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                      |
| Protection against electric shock         | <b>I</b>                                        |
| Protection degree                         | <b>IP20</b>                                     |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                    |
| Lifetime of LED sources [h]               | <b>100000</b>                                   |
| Lx/By                                     | <b>L80/B10</b>                                  |
| Operating temperature range [°C]          | <b>5 ÷ 35</b>                                   |
| Driver                                    | <b>standard on/off (E)</b>                      |

**Mechanical data**



|                  |                           |
|------------------|---------------------------|
| Assembly         | surface mounted on slings |
| Material         | steel sheet               |
| Color            | RAL 9016 (white)          |
| Diffuser         | PLX (PMMA opal)           |
| Impact resistant | IK04                      |
| Dimensions [mm]  | 1125 x 162 x 75           |

**A graph of light**



## Accessories

Index 0E1ALLS-SP

Name AGALINE LED CONNECTOR



Index 0E1ALLS-AE

Name AGALINE LED END-CAP  
PLX/MICRO-PRM/MICRO-  
LINE/ODB 34



Index 1E1AL8030-2-2

Name COVER 8030-2-2 RAL9016



Index 0E1ALLS-SPM

Name AGALINE LED Connecting points  
cover ODB 34



Index 6E1-500KW34K-3

Name SUSPENSION NEW TYPE-A+B 34  
LENGHT 1,5M WIRE 3X SET



Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F  
LENGHT-1,5 METER WIRE 3X 1-  
POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT



Index 6E1-500KWB34K-3

Name SUSPENSION NEW TYPE-A+E 34  
LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D  
LENGHT-1,5 METER WIRE 3X 1-  
POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C  
LENGHT-1,5 METER WITHOUT  
WIRE 1-POINT

