


Product: AGALINE LED 16000 EDD 34 840 / L-2245MM Index: 19.4212.4123.34



Description

Agaline is an industrial modular system for installing in straight lines. Agaline is an excellent option for lighting industrial premises and warehouses, but is also suitable for offices, supermarkets and commercial spaces. A luminaire mounted in line systems, made of sheet steel, painted in white. Individual elements of the system combined with connectors. Through-cabling ensures easy and fast installation. To be applied in industrial objects and other places, where high intensity and uniformity of lighting is necessary. ATTENTION: Lenght 2805mm for special request.


Product information	Category	Industrial luminaire	S	
	Family	AGALINE LED		
	Name	AGALINE LED 1600) EDD 34 840 / L-2245MM	
	Index	19.4212.4123.34		
	EAN	5902107427764		
		$\overbrace{ED} \textcircled{ED} \end{array}{ED} \end{array}{ED} \end{array}{ED} \textcircled{ED} \textcircled{ED} \textcircled{ED} \textcircled{ED} \textcircled{ED} \textcircled{ED} \end{array}{ED} \end{array}{ED} \end{array}{ED} \textcircled{ED} \textcircled{ED} \textcircled{ED} \end{array}{ED} $ {ED} \end{array}{ED} \end{array}{ED} \end{array}{ED} {ED} {ED} {ED}		
Light and electrical data	Light source		LED	
	Luminous flu	x LED [lm]	17396	
	LED power [(V)	82,4	
	Luminaire lu	minous flux [lm]	17396	
	Power of lum	iinaire [W]	92,3	
	Luminaire's l	ight efficiency [lm/W]	188,5	
	Color of the	ight [K]	4000	
	CRI		>80	
	SDCM (LED	sources)	3	
	Beam angle	[°]	(C0-C180) / (C90-C270) - 114,4° / 114,4°	
	Photobiologi 62471)	cal risk class (IEC/EN	RG0	
	Protection ag	jainst electric shock	I	
	Protection de	egree	IP20	
	Voltage		220240 V, 5060 Hz	
	Lifetime of L	ED sources [h]	100000	
	Lx/By		L80/B10	
	Operating te	mperature range [°C]	5 ÷ 35	
	Driver		DIM DALI (EDD)	
Mechanical data	Assembly		surface mounted on slings	
	Material		steel sheet	
H				
A B	Color		RAL 9016 (white)	
AB	Color Diffuser		RAL 9016 (white) none	
		ant		








Accessories





Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 5X SET




- Index 6E1-9875-4-1,5-5X
- Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



- Name AGALINE LED END-CAP 34
- Index 6E1-8670-B-1,5-5X Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 5X 1-POINT



- Index 6E1-9875-3-1,5 Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT
 - WIRE 1-POINT




Index 19.3272.1205.00

Index OE1ALLS-EP

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 1E1AL8030-4-2

Name COVER 8030-4-2 RAL9016

Index 6E1-500KWB34K-5

Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 5X SET



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025