

Product: AGALINE LED 32000 ODB PLX E 34 830 / L-2245MM

Index: 19.4212.7311.34



Description

Agaline is an industrial modular system for installing in straight lines. Agaline is an excellent option for lighting industrial premises and warehouses, but is also suitable for offices, supermarkets and commercial spaces. A luminaire mounted in line systems, made of sheet steel, painted in white. Individual elements of the system combined with connectors. Through-cabling ensures easy and fast installation. To be applied in industrial objects and other places, where high intensity and uniformity of lighting is necessary. ATTENTION: Lenght 2805mm for special request.

Product information

| Category | Industrial luminaires |
|----------|---|
| Family | AGALINE LED |
| Name | AGALINE LED 32000 ODB PLX E 34 830 / L-2245MM |
| Index | 19.4212.7311.34 |
| FAN | 5902107428136 |
















Light and electrical data

| Light source | LED |
|---|---|
| Luminous flux LED [lm] | 33056 |
| LED power [W] | 164,8 |
| Luminaire luminous flux [lm] | 26775,4 |
| Power of luminaire [W] | 184,6 |
| Luminaire's light efficiency [lm/W] | 145 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 108,6° / 109,4° |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | standard on/off (E) |


Mechanical data



| Assembly | surface mounted on slings |
|------------------|---------------------------|
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Dimensions [mm] | 2245 x 162 x 75 |



A graph of light







Accessories

Index 0E1ALLS-SP

Name AGALINE LED CONNECTOR



Index OE1ALLS-AE

Name AGALINE LED END-CAP PLX/MICRO-PRM/MICRO-LINE/ODB 34



Index 1E1AL8030-4-2

Name COVER 8030-4-2 RAL9016



Index OE1ALLS-SPM

Name AGALINE LED Connecting points cover ODB 34





Index 6E1-500KW34K-3

Name SUSPENSION NEW TYPE-A+B 34 LENGHT 1,5M WIRE 3X SET




Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB34K-3




Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Name SUSPENSION NEW TYPE-A+E 34 LENGHT 1,5M WIRE 3X SET

