

Product: NEPTUN LED V2 4400 PC-FROZEN EDD IP66 21 840 / 1200x72x58MM HT50

Index: 19.4218.1123.21



Description

Tightly-closed ceiling luminaries with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminary is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminary is dedicated for rooms with elevated air temperatures.

Product information

Category	Industrial luminaires
Family	NEPTUN LED V2
Name	NEPTUN LED V2 4400 PC-FROZEN EDD IP66 21 840 / 1200x72x58MM HT50
Index	19.4218.1123.21











Light and electrical data

Light source	LED		
Luminous flux LED [lm]	5268,3		
LED power [W]	25		
Luminaire luminous flux [lm]	4897,9		
Power of luminaire [W]	27,8		
Luminaire's light efficiency [lm/W]	176,2		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 119,4° / 104°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP66		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000		
Lx/By	L80/B10		
Operating temperature range [°C]	-40 ÷ 50		
Driver	DIM DALI (EDD)		
Power factor cos φ	>0,95		
Circuit load capacity	20 (B10), 32 (B16), 25 (C10), 40 (C16)		



Mechanical data

Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polycarbonate
Color	RAL 9006 (grey)
Diffuser	PC-FROZEN (frozen polycarbonate)
Impact resistant	IK10
Dimensions [mm]	1200 x 72 x 58

A graph of light



Accessories

Index 19.3206.0071.21

Name NEPTUN LED V2 UCHWYT REGULOWANY 21 KPL.







