

**Product:** NEPTUN INDUSTRY LED 12000 PC-T OPTICS-ASY E 21 IP66 840 / 1563X115X110 MM HT50

**Index:** 19.4344.6521.21



## Description

Tightly-closed ceiling luminaires with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminaire is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. Luminaire designed for industrial facilities, for ambient temperatures up to +50° C. Optical system based on lenses.

## Product information

Category	<b>Industrial luminaires</b>
Family	<b>NEPTUN INDUSTRY LED OPTICS HT50</b>
Name	<b>NEPTUN INDUSTRY LED 12000 PC-T OPTICS-ASY E 21 IP66 840 / 1563X115X110 MM HT50</b>
Index	<b>19.4344.6521.21</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>12055</b>
LED power [W]	<b>58,5</b>
Luminaire luminous flux [lm]	<b>10493,3</b>
Power of luminaire [W]	<b>66,5</b>
Luminaire's light efficiency [lm/W]	<b>157,8</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>asymmetric light distribution</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>90000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 50</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>20 (B10), 32 (B16), 25 (C10), 40 (C16)</b>

## Mechanical data



Assembly	<b>directly mounted to ceiling construction or surface mounted on slings</b>
Material	<b>polycarbonate</b>
Color	<b>RAL 9006 (grey)</b>
Diffuser	<b>PC-T (transparent polycarbonate)</b>
Impact resistant	<b>IK10</b>
Dimensions [mm]	<b>1563 x 115 x 110</b>

## A graph of light

