

**Product:** AMETYST NEW LED COMPACT 3000 PC E IP65 34 830

**Index:** 19.4347.1211.34



## Description

Surface mounted or wall luminaire equipped in highly efficient LED panels. Luminaire body and diffuser made from IK10 impact resistant material. High level of protection against penetration of dust and water - IP65. Luminaire recommended for: bathrooms, wards, medical staff room.

## Product information

Category	<b>Compact</b>
Family	<b>AMETYST NEW LED COMPACT</b>
Name	<b>AMETYST NEW LED COMPACT 3000 PC E IP65 34 830</b>
Index	<b>19.4347.1211.34</b>
EAN	<b>5902107208905</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>2982</b>
LED power [W]	<b>18,1</b>
Luminaire luminous flux [lm]	<b>2348</b>
Power of luminaire [W]	<b>18,6</b>
Luminaire's light efficiency [lm/W]	<b>126,2</b>
Color of the light [K]	<b>3000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 112,6° / 112,4°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP65</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>80000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-20 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>29 (B10), 47 (B16), 49 (C10), 79 (C16)</b>

**Mechanical data**



Assembly	surface mounted on ceiling or on wall
Material	polycarbonate
Color	RAL 9016 (white)
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Weight [kg]	1,23
Dimensions [mm]	Ø356 x 76

**A graph of light**

