

Product: X-WALL R LED 2200 PC OPAL EDD IP44 24 827-865 / L-580mm TUNABLE WHITE

Index: 19.4348.1353.24



Description

Luminaires designed for surface mounting. Made of aluminium with an opal polycarbonate diffuser, they include highly efficient LEDs. Easy-to-install, specifically recommended for damp areas.

Product information

| Category | Surface mounted luminaires |
|----------|---|
| Family | X-WALL R LED |
| Name | X-WALL R LED 2200 PC OPAL EDD IP44 24 827-865 / L-580mm TUNABLE WHITE |
| Index | 19.4348.1353.24 |
| EAN | 5902107293444 |
















Light and electrical data

| Light source | LED |
|-------------------------------------|---|
| Luminous flux LED [lm] | 2157÷2275 (2700÷6500 K) |
| LED power [W] | 13÷15 (6500÷2700 K) |
| Luminaire luminous flux [lm] | 1589÷1676 (2700÷6500 K) |
| Power of luminaire [W] | 16 |
| Luminaire's light efficiency [lm/W] | 99÷105 (2700÷6500 K) |
| Color of the light [K] | 2700 ÷ 6500 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | asymmetric light distribution - Imax=-49,5 $^{\circ}$ |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 50000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 17 (B10), 28 (B16), 26 (C10), 42 (C16) |

Mechanical data





| Assembly | mounted on wall |
|------------------|-------------------------------|
| Material | aluminum |
| Color | anodised aluminum |
| Diffuser | PC (opalescent polycarbonate) |
| Impact resistant | IK04 |
| Dimensions [mm] | 580 x 56 x 60 |



A graph of light

