

Product: X-WALL R LED 4400 PC OPAL E IP44 24 840 / L-1140MM

Index: 19.4348.3721.24



Description

Luminaires designed for wall mounting. Made of aluminium with an opal polycarbonate diffuser, they include highly efficient LEDs. Easy-to-install, specifically recommended for damp areas.

Product information

Category	Surface mounted luminaires
Family	X-WALL R LED
Name	X-WALL R LED 4400 PC OPAL E IP44 24 840 / L-1140MM
Index	19.4348.3721.24
EAN	5902107293536



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4565
LED power [W]	23,4
Luminaire luminous flux [lm]	3363
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	136,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-49,5°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK04
Weight [kg]	1,9
Dimensions [mm]	1140 x 56 x 60

A graph of light

