

Product: NEPTUN LED COMPACT V2 2600 PC-FROZEN EDD IP66 21 840 / 1200X72X58MM

Index: 19.4351.1123.21



Description

Tightly-closed ceiling luminaries with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminary is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminary is dedicated for halls, warehouses, underground passes, car parks illumination etc.

Product information

Category	Compact
Family	NEPTUN LED COMPACT V2
Name	NEPTUN LED COMPACT V2 2600 PC-FROZEN EDD IP66 21 840 / 1200X72X58MM
Index	19.4351.1123.21
EAN	5902107295837














Light and electrical data

Light source	LED
Luminous flux LED [lm]	2864
LED power [W]	14,2
Luminaire luminous flux [lm]	2662,6
Power of luminaire [W]	15,8
Luminaire's light efficiency [lm/W]	168,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 119,4° / 104°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	
i rotection degree	IP66
Voltage	IP66 220240 V, 5060 Hz
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 80000
Voltage Lifetime of LED sources [h] Lx/By	220240 V, 5060 Hz 80000 L80/B10
Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	220240 V, 5060 Hz 80000 L80/B10 -20 ÷ 40



Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polycarbonate
Color	RAL 9006 (grey)
Diffuser	PC-FROZEN (frozen polycarbonate)
Impact resistant	IK10
Dimensions [mm]	1200 x 72 x 58

A graph of light

Accessories

Index 19.3206.0071.21

Name NEPTUN LED V2 UCHWYT REGULOWANY 21 KPL.





Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 22-08-2025