

Product: NEPTUN LED COMPACT V2 11000 PC-OPAL E IP66 21 840 / 1200X92X60MM ZASILANIE PRZELOTOWE 16A

Index: 19.4352.5621.21



Description

Tightly-closed ceiling luminaries with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminary is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminary is dedicated for halls, warehouses, underground passes, car parks illumination etc. Looping through power supply 16 A.

Product information

Category	Compact
Family	NEPTUN LED COMPACT V2
Name	NEPTUN LED COMPACT V2 11000 PC-OPAL E IP66 21 840 / 1200X92X60MM ZASILANIE PRZELOTOWE 16A
Index	19.4352.5621.21
EAN	5902107426514



Light and electrical data


Light source	LED
Luminous flux LED [lm]	11530
LED power [W]	60
Luminaire luminous flux [lm]	9551,5
Power of luminaire [W]	67,4
Luminaire's light efficiency [lm/W]	141,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 107,2° / 134,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L80/B10
Operating temperature range [°C]	-25 ÷ 40
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polycarbonate
Color	RAL 9006 (grey)
Diffuser	PC-OPAL (opalescent polycarbonate)
Impact resistant	IK10
Dimensions [mm]	1200 x 92 x 60

A graph of light



Accessories

Index	19.3206.0071.21
Name	NEPTUN LED V2 UCHWYT REGULOWANY 21 KPL.

