

Product: X-WALL K9 LED 4400 PLX E IP44 24 830 / L-1135MM

Index: 19.4354.4411.24



Description

Surface mounted and wall luminary. Luminary body made from aluminum profile, its diffuser made from PMMA. Its asymmetric optical system together with the diffuser provides high energetic efficiency. Luminary recommended for: hospital bathrooms and wards.

Product information

Category	Surface mounted luminaires
Family	X-WALL K9 LED
Name	X-WALL K9 LED 4400 PLX E IP44 24 830 / L-1135MM
Index	19.4354.4411.24
EAN	5901867466006
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	4406
LED power [W]	23,4
Luminaire luminous flux [lm]	2877
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	116,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-47°
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lifetime of LED sources [h]	,
	100000 (1) / 147000 (2)
Lx/By	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Lx/By Operating temperature range [°C]	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30

Mechanical data





Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,79
Dimensions [mm]	1134 x 50 x 60



A graph of light

