

Product: X-WALL K9 LED 5200 PLX E IP44 24 840 / L-2255MM

Index: 19.4355.7721.24



Description

Surface mounted and wall luminary. Luminary body made from aluminum profile, its diffuser made from PMMA. Its asymmetric optical system together with the diffuser provides high energetic efficiency. Luminary recommended for: hospital bathrooms and wards.

Product information

Category	Surface mounted luminaires
Family	X-WALL K9 LED
Name	X-WALL K9 LED 5200 PLX E IP44 24 840 / L-2255MM
Index	19.4355.7721.24
EAN	5901867432384
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	5234
LED power [W]	26,6
Luminaire luminous flux [lm]	3418
Power of luminaire [W]	28,2
Luminaire's light efficiency [lm/W]	121,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-47°
Protection against electric shock	I
Protection degree	IP44
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

Mechanical data





Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	2,82
Dimensions [mm]	2255 x 50 x 60



A graph of light

