

**Product:** X-WALL K9 LED 1300 PLX EDD IP44 24 840 / L-575MM**Index:** 19.4355.2223.24

## Description

Surface mounted and wall luminary. Luminaire body made from aluminum profile, its diffuser made from PMMA. Its asymmetric optical system together with the diffuser provides high energetic efficiency. Luminaire recommended for: hospital bathrooms and wards.

## Product information


Category	Surface mounted luminaires
Family	X-WALL K9 LED
Name	X-WALL K9 LED 1300 PLX EDD IP44 24 840 / L-575MM
Index	19.4355.2223.24



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	1420
LED power [W]	8
Luminaire luminous flux [lm]	927
Power of luminaire [W]	9
Luminaire's light efficiency [lm/W]	103
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-47°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,9
Circuit load capacity	14 (B10), 24 (B16), 22 (C10), 36 (C16)

## Mechanical data



Assembly	mounted on wall
Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1
Dimensions [mm]	574 x 50 x 60

A graph of light

