

Product: RUBIN ROUND 800 LED 9800 PLX E 21 840 / H-180MM

Index: 19.4357.1921.21



Description

The fitting is used in public buildings such as banks, offices, hotels, stores, schools, that is wherever pleasant environment is of special importance. Rubin O gives the interior style and individuality. The special construction of this fitting and its diffusers permit to restrict glare. The housing is made of steel plate, powder painted, diffusers applied are opal.

Product information

Category	Surface mounted luminaires	
Family	RUBIN ROUND LED	
Name	RUBIN ROUND 800 LED 9800 PLX E 21 840 / H-180MM	
Index	19.4357.1921.21	
EAN	5902107011499	















Light and electrical data

Links around	1.50
Light source	LED
Luminous flux LED [lm]	10200
LED power [W]	50
Luminaire luminous flux [lm]	6915
Power of luminaire [W]	56
Luminaire's light efficiency [lm/W]	123,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 107,4° / 107,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220 240 1/ 50 00 11-
	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
	•
Lifetime of LED sources [h]	60000
Lifetime of LED sources [h] Lx/By	60000 L80/B10
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	60000 L80/B10 5 ÷ 30




Mechanical data





Assembly	directly mounted to ceiling construction or surface mounted on slings using accessories
Material	steel sheet
Color	RAL 9006 (grey, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	12,61
Dimensions [mm]	Ø800 x 188

A graph of light



Accessories

Index 6E1-5000K211P-3

Name SUSPENSION NEW TYPE-J 21 LENGHT 1,5M WIRE 3X 1-POINT



Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

