

Product: METEOR LUX LED 5200 OPAL EDD 34 840 L-1255MM

Index: 19.4358.1323.34



## **Description**

Surface mounted luminaries equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminary mounted directly on ceilings by raw plugs.

### **Product information**

Category	Surface mounted luminaires
Family	METEOR LUX LED
Name	METEOR LUX LED 5200 OPAL EDD 34 840 L-1255MM
Index	19.4358.1323.34
EAN	5902107091224















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5344
LED power [W]	24,8
Luminaire luminous flux [lm]	4283,1
Power of luminaire [W]	27,6
Luminaire's light efficiency [lm/W]	155,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 121,6° / 110,4°
Photobiological risk class (IEC/EN	RG0
62471)	
62471) Protection against electric shock	1
	I IP20
Protection against electric shock	•
Protection against electric shock Protection degree	IP20
Protection against electric shock Protection degree Voltage	IP20 220240 V, 5060 Hz
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h]	IP20 220240 V, 5060 Hz 100000
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP20 220240 V, 5060 Hz 100000 L80/B10
Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP20 220240 V, 5060 Hz 100000 L80/B10 -20 ÷ 35



## **Mechanical data**



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PMMA opal
Impact resistant	IK04
Weight [kg]	2,3
Dimensions [mm]	1255 x 207 x 71

# A graph of light







