

Product: METEOR LUX LED 2600 OPAL E IP44 34 840 L-1255MM

Index: 19.4358.2121.34



Description

Surface mounted luminaires equipped with highly efficient LED sources. Luminaire base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminaire mounted directly on ceilings by raw plugs.

Product information


Category	Surface mounted luminaires
Family	METEOR LUX LED
Name	METEOR LUX LED 2600 OPAL E IP44 34 840 L-1255MM
Index	19.4358.2121.34
EAN	5902107156534



Light and electrical data

Light source	LED
Luminous flux LED [lm]	2672
LED power [W]	12,4
Luminaire luminous flux [lm]	2141,6
Power of luminaire [W]	13,8
Luminaire's light efficiency [lm/W]	155,2
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 121,6° / 110,4°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PMMA opal
Impact resistant	IK04
Weight [kg]	2,2
Dimensions [mm]	1255 x 207 x 71

A graph of light

