

Product: RUBIN LOOK LED 2600 PLX E 34 830 / 595X320MM

Index: 19.4360.4211.34



Description

Surface mounted luminary for LED sources. Luminary body made from steel sheet, powder coated. Luminary recommended for: wards and hospital bathrooms.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED
Name	RUBIN LOOK LED 2600 PLX E 34 830 / 595X320MM
Index	19.4360.4211.34
EAN	5901867467782















Light and electrical data

Linkt assumes	1.50	
Light source	LED	
Luminous flux LED [lm]	2525	
LED power [W]	13,3	
Luminaire luminous flux [lm]	1844	
Power of luminaire [W]	14,4	
Luminaire's light efficiency [lm/W]	128,1	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 102,8° / 102,8°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP40	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000 (1) / 147000 (2)	
Lx/By	L80/B10 (1) / L70/B50 (2)	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)	



Mechanical data	Assembly	surface mounted on ceiling
	Material	steel sheet
	Color	RAL 9016 (white)
В	Diffuser	PLX (PMMA opal)
L TH	Impact resistant	IK04
A	Weight [kg]	2,3
	Dimensions [mm]	595 x 320 x 55

A graph of light

