

Product: RUBIN LOOK LED 5200 PLX E 34 840 / 595X595MM

Index: 19.4360.7621.34



Description

Surface mounted luminaire for LED sources. Luminaire body made from steel sheet, powder coated. Luminaire recommended for: wards and hospital bathrooms.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED
Name	RUBIN LOOK LED 5200 PLX E 34 840 / 595X595MM
Index	19.4360.7621.34
EAN	5902107019280



Light and electrical data

Light source	LED
Luminous flux LED [lm]	5234
LED power [W]	26,6
Luminaire luminous flux [lm]	3822
Power of luminaire [W]	28,2
Luminaire's light efficiency [lm/W]	135,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 102,8° / 102,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,1
Dimensions [mm]	595 x 595 x 55

A graph of light

