

**Product: RUBIN LOOK LED 3300 PLX E 34 840 / 417X417MM** 

Index: 19.4360.1321.34



### **Description**

Surface mounted luminary for LED sources. Luminary body made from steel sheet, powder coated. Luminary recommended for: wards and hospital bathrooms.

### **Product information**

Category	Surface mounted luminaires
Family	RUBIN LOOK LED
Name	RUBIN LOOK LED 3300 PLX E 34 840 / 417X417MM
Index	19.4360.1321.34
EAN	5901867467683
















### Light and electrical data

Light source	LED
Luminous flux LED [lm]	3436
LED power [W]	17,4
Luminaire luminous flux [lm]	2509
Power of luminaire [W]	19,2
Luminaire's light efficiency [lm/W]	130,7
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 102,8° / 102,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
•	
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lifetime of LED sources [h]	,
	100000 (1) / 147000 (2)
Lx/By	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Lx/By Operating temperature range [°C]	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30



## Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,99
Dimensions [mm]	417 x 417 x 55

# A graph of light

