

**Product:** RUBIN LOOK LED 3900 PLX EDD IP44 34 840 / 620X625MM**Index:** 19.4361.7423.34

## Description

Surface mounted luminary for LED sources. Luminary body made from steel sheet, powder coated. Luminary recommended for: wards and hospital bathrooms. Dust, and humidity penetration: IP44.

## Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED IP44
Name	RUBIN LOOK LED 3900 PLX EDD IP44 34 840 / 620X625MM
Index	19.4361.7423.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	3926
LED power [W]	20
Luminaire luminous flux [lm]	2794
Power of luminaire [W]	21,7
Luminaire's light efficiency [lm/W]	128,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 108,2° / 107,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	6,84
Dimensions [mm]	620 x 625 x 61

A graph of light

