

Product: RUBIN LOOK LED S SMOOTH 7500 PLX EDD IP44 34 840 / 1140X368MM

Index: 19.4363.1423.34



Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED SMOOTH
Name	RUBIN LOOK LED S SMOOTH 7500 PLX EDD IP44 34 840 / 1140X368MM
Index	19.4363.1423.34
EAN	5902107073206



Light and electrical data

Light source	LED
Luminous flux LED [lm]	7875
LED power [W]	39,8
Luminaire luminous flux [lm]	5924
Power of luminaire [W]	42,2
Luminaire's light efficiency [lm/W]	140,4
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 13 (B16), 13 (C10), 21 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1140 x 368 x 56

A graph of light

